

Cabinet cooling unit



Description

| | |
|----------------------------|--------------------------------|
| Order Number: | 850510S62 |
| Brand Name: | SLIMLINE PRO |
| Housing Material: | Stainless steel AISI 304 (V2A) |
| Ingress Protection: | IP 56 / Type 12, 3, 3R, 4, 4X |
| Approvals: | CE, cURus, cULus |

Technical Data

Cooling capacity L35L35 (EN14511-3): 650 W

Cooling capacity L35L50 (EN14511-3): 395 W

EER L35L35: 1.41

Compressor type: Rotary piston

Refrigerant / GWP: R134a / 1430

Refrigerant charge: 103 g / 3.63 oz

High / low Pressure: 25 / 6 bar
363 / 87 psi

Operating Temperature Range: 10°C - 60°C

UL temperature range: 10°C - 55°C

Air flow volume (system / unimpeded): Ambient air circuit: 200 / 408 m³/h
Cabinet air circuit: 122 / 180 m³/h

Mounting: Wall mounted / recessed

Dimensions A x B x C (D+E): 370 x 520 x 155 (60+95) mm

Weight: 16 kg

Voltage / Frequency: 120 V ~ 60 Hz

UL Voltage / Frequency: 120 V ~ 60 Hz

Current L35L35: 4.1 A

Starting current: 13 A

Max. current: 5.3 A

Nominal power L35L35: 460 W

Max. power: 610 W

Fuse: 15 A (T)

Max circuit ampacity: 15 A

Short-circuit current rating: 5 kA

Rated current compressor: 3.7 A

Full load current fans: 0.4 A

Connection: 4 pole terminal block for electrical connection
5 pole terminal block for signals
3 pole terminal block for RS 485




Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

Performance graph:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

| | |
|-----------------------|-----------------------|
| Box dimensions | 460 x 620 x 181.75 mm |
| Gross weight | 20 Kg |
| Taric code | 84158200 |