

Enclosure air conditioner



Description

Order Number:	841210S62
Brand Name:	SLIMLINE PRO
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Note:	Hat denselben Schaltschrankausbruch wie KG 8508 und KG 8512
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	5120 BTU @ 50 Hz 5290 BTU @ 60 Hz
Cooling capacity 95F/122F:	4330 BTU @ 50 Hz 4540 BTU @ 60 Hz
EER 95F95F:	2.20
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	267 g / 9.4 oz.
High / low pressure:	30 / 6 bar 435 / 88 psi
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 140°F
Air volume flow (system / unimpeded):	Ambient: 323 / 500 m³/h Enclosure: 206 / 500 m³/h
Mounting:	Wall mounted / recessed
Dimension H x W x D:	37.5 x 15.6 x 9.9 inch
Weight:	99 lbs
Voltage / Frequency:	120 V ~ 50/60 Hz
UL Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	6.4 A @ 50 Hz 7.2 A @ 60 Hz
Starting current:	32 A
Max. current:	9.4 A
Nominal power 95F95F:	680 W @ 50 Hz 830 W @ 60 Hz
Max. power:	1.1 kW
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	5 A

Full load current fans: 1.5 A

Connection: 4 - poliger Stecker für Versorgungsspannung
5 - poliger Stecker für Signale
3 - poliger Stecker für RS 485

Cut out dimensions:



Order Information

Box dimensions	1042 x 495 x 283 mm
-----------------------	---------------------

Gross weight	46 Kg
---------------------	-------

Taric code	84158200
-------------------	----------