

SlimLine HEx - Air / Water Heat Exchanger



Description

Order Number:	752500B001
Brand Name:	SLIMLINE HEX
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 55 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus

Technical Data

Cooling capacity L35W10 (500 l/h):	2800 W
Coolant:	Water, light oils or similar
Operating Temperature Range:	1°C - 60°C
Air flow volume (system / unimpeded):	560 / 800 m³/h
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	1,350 x 395 x 192 (37+155) mm
Weight:	28 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Starting current:	0.6 / 0.6 A
Max. current:	0.4 / 0.5 A
Max. power:	90 / 110 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/2" - inside thread (with optional connectors for pipe internal diameter of 13 mm)
Fuse:	1 A (T)
Connection:	5 - pole terminal for signals 4 - pole terminal for power

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE HEX - air/water heat exchangers](#)

3/4

Order Information

Stainless steel AISI 304 (V2A) housing order no.	752500B62
Box dimension	1442 x 495 x 242 mm
Gross weight	35 kg
Taric code	84158300