# Filter Fan



## Description

| | |
|---|---|
| **Order Number:** | 4023A3000 |
| **Brand Name:** | SOLIFLEX |
| **Colour:** | RAL 7035 |
| **Housing Material:** | ABS Plastic |
| **Ingress Protection:** | IP 54, Type 12, 3R |
| **Optional:** | Different housing colors available on request |
| **Approvals:** | CE, cURus, cULus, CSA |
| **Accessories:** |  Hose-proof protection hood FC 4000 000 |
| |  Hose-proof protection hood FC 4000 000 FDA |
| |  Adjustable Thermostat NO |


## Technical Data

| | |
|---|---|
| **Operating Temperature Range:** | -10°C - 55°C |
| **Air flow unimpeded:** | 26 m³/h |
| **Static pressure:** | 57 Pa |
| **Dimensions A x B x C (D+E):** | 106.5 x 106.5 x 79.5 mm |
| **Weight:** | 0.54 kg |
| **Cut out dimensions:** | 92.5 x 92.5 (+0.5) mm |
| **Voltage / Frequency:** | 120 V ~ 60 Hz |
| **Rated current:** | 0.13 A |
| **Power consumption:** | 10 W |
| **Degree of separation:** | 85% - DIN 24185 |
| **Wall thickness:** | 1 - 2 mm |
| **Filter class:** | G3 according to EN 779 |
| **Installation:** | Elastic clips |
| **Noise level:** | 42 dB(A) |

Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters


**Air flow:**

Q = Air flow [m3/h]
P = Static pressure [Pa]




click image to enlarge

**Cut Out Dimension**:




click image to enlarge

## Order Information

| | |
|---|---|
| **In RAL 9005** | 4023A3003 |
| **With TYPE 3R protection part no.** | 4023A3030 |
| **Taric code** | 84145915 |
| **GTIN (EAN)** | 5350604100190 |