Filter Fan

Description

Order Number:	4210D7100
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54
Note:	Reverse air flow
Optional:	Different housing colours available on request
Approvals:	CE, cURus, cULus, CSA
Accessories:	Hose-proof protection hood FC 4000 100 Hose-proof protection hood FC 4000 100 FDA

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	64 m³/h
Static pressure:	79 Pa
Dimensions A x B x C (D+E):	150 x 150 x 73 mm
Weight:	0.5 kg
Cut out dimensions:	124 x 124 (+1.5) mm
Voltage / Frequency:	48 V DC
Rated current:	0.18 A
Power consumption:	8.6 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1 - 2.1 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	48 dB(A)

Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters

Air flow:

Q = Air flow [m3/h]
P = Static pressure [Pa]



click image to enlarge

Cut Out Dimension:





click image to enlarge

Order Information

In RAL 9005	4210D7103
Taric code	84145915
GTIN (EAN)	5350604100299