

Filter Fan



Description

Order Number:	4611D2100
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54
Optional:	Different housing colours available on request With NEMA 3R protection part no. 4611D2130
Approvals:	CE, cULus, CSA

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	150 m³/h
Static pressure:	84 Pa
Dimensions A x B x C (D+E):	250 x 250 x 111.6 mm
Weight:	0.9 kg
Cut out dimensions:	223 +1.5 x 223 +1.5 mm
Voltage / Frequency:	24 V DC
Rated current:	0.32 A
Power consumption:	7.6 W
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 gemäß EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	42 dB(A)


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

With NEMA 3R protection part no.	4611D2130
Taric code	84145915
GTIN (EAN)	5350604100497