Filter Fan



Description


Order Number:	4830A3000
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus
Accessories:	 Hose-proof protection hood FC 4000 400
	 Hose-proof protection hood FC 4000 400 FDA
	 Adjustable Thermostat NO

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	485 m³/h
Static pressure:	190 Pa
Dimensions A x B x C (D+E):	325 x 325 x 160.2 mm
Weight:	3.62 kg
Cut out dimensions:	291 x 291 (+1.5) mm
Voltage / Frequency:	120 V ~ 60 Hz
Rated current:	0.73 A
Power consumption:	83 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	69.2 dB(A)


Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters

Air flow:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

In RAL 9005	4830A3003
With TYPE 3R protection part no.	4830A3033
Taric code	84145915
GTIN (EAN)	5350604100619