

Outdoor cooling unit



Description

Order Number:	4109100
Brand Name:	Compact Outdoor
Housing Material:	Aluminum
Ingress Protection:	IP 55
Approvals:	CE, cURus

Technical Data

Cooling capacity L35L35:	1,35 kW @ 60 Hz
Cooling capacity L35L50:	885 W @ 60 Hz
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	400 g / 14.1 oz
High / low Pressure:	27 / 6 bar 400 / 88 psig
Operating Temperature Range:	+10°C - +50°C
Air flow volume (system / unimpeded):	Ambient air circuit: 480 / 688 m³/h Cabinet air circuit: 360 / 850 m³/h
Mounting:	Internal
Dimensions A x B x C (D+E):	1,025 x 466.5 x 157 mm
Weight:	30 kg
Voltage / Frequency:	120 V ~ 60 Hz
Current L35L35:	7.9 A
Starting current:	40 A
Max. current:	9.4 A
Nominal power L35L35:	820 W
Max. power:	975 W
Fuse:	16 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

