

Filter Fan



Description

Order Number:	4880A4100
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54
Optional:	Different housing colours available on request
Approvals:	CE, cULus, CSA

Technical Data

Operating Temperature Range:	-10°C - +55°C
Air flow unimpeded:	720 m³/h - 820 m³/h
Static pressure:	290 Pa @ 50 Hz 280 Pa @ 60 Hz
Mounting:	Elastic clips or by 4 self-threading screws
Dimensions A x B x C (D+E):	325 x 325 x 158.5 mm
Weight:	4.25 kg
Cut out dimensions:	291 x 291 mm (+1.5)
Voltage / Frequency:	230V - 50/60 Hz
Rated current:	0.53 A / 0.69 A
Power consumption:	120 W / 157 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	66 dB(A) @ 50 Hz 69.2 dB(A) @ 60 Hz


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)