

Cooling unit NEMA / type 4X



Description


Order Number:	57050162
Brand Name:	Compact Outdoor
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data

Cooling capacity L35L35:	550 W @ 50 Hz 570 W @ 60 Hz
Cooling capacity L35L50:	445W @ 50 Hz 490 W @ 60 Hz
Enclosure heater:	400 W
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
High / low Pressure:	29.3 / 6.1 bar 425 / 88 psig
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 315 / 850 m³/h Cabinet air circuit: 165 / 250 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	830 x 304 x 270 mm
Weight:	30 kg
Cut out dimensions:	265 x 180 mm 265 x 160 mm
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group COMPACT OUTDOOR - OLD](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

In stainless steel 304 (V2A) part no.	57050062
With stainless steel 316 (V4A) part no.	57050064
In stainless steel 304 (V2A) with 400 W enclosure heater part no.	57050162
In stainless steel 316 (V4A) with 400 W enclosure heater part no.	57050164
Box dimensions	870 x 348 x 310 mm
Gross weight	32 kg
Taric code	84158200