Control Cabinet Air Conditioner



Description

Order Number:	43082081
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus


Accessories:



Stainless Steel Filter Holder 4305/08/09/10



Fibre Filter Media 4304




Washable Aluminium Filter 4305/08/09/10

Technical Data

Cooling capacity L35L35:	750 W @ 50 Hz 780 W @ 60 Hz
Cooling capacity L35L50:	580 W @ 50 Hz 610 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 435 / 550 m³/h Cabinet air circuit: 200 / 250 m³/h
Mounting:	Recessed
Dimensions A x B x C (D+E):	715 x 372 x 260 (170+90) mm
Cut out dimensions:	316 x 654 mm
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group COMPACT INDOOR - reliable and economical

Performance graph:




click image to enlarge

Air flow:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

Stainless steel housing part no.	43082026
Taric code	84158200