Filter Fan



Description

Order Number:	4883A9003
Brand Name:	SOLIFLEX
Colour:	RAL 9005
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Accessories:



Hose-proof protection hood FC 4000 400



Hose-proof protection hood FC 4000 400 FDA



Adjustable Thermostat NO


Technical Data

Operating Temperature Range:	-10°C - +70°C
Air flow unimpeded:	820 m³/h - 930 m³/h
Dimensions A x B x C (D+E):	325 x 325 x 158.5 mm
Weight:	4.25 kg
Cut out dimensions:	291 x 291 (+1.5) mm
Voltage / Frequency:	400/460 V ~ 50/60 Hz
Rated current:	0.20 A / 0.24 A
Power consumption:	110 / 145 W
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 gemäß EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	66 dB(A) @ 50 Hz 69.2 dB(A) @ 60 Hz

Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters


Air flow:


Q = Air flow [cfm]
P = Static pressure [inH2O]



click image to enlarge

Cut Out Dimension:





click image to enlarge

Order Information

Taric code	84145915
GTIN (EAN)	5350604100848