

## Cooling unit NEMA / type 4X



### Description


|                            |                                  |
|----------------------------|----------------------------------|
| <b>Order Number:</b>       | 57041162                         |
| <b>Brand Name:</b>         | Compact Outdoor                  |
| <b>Housing Material:</b>   | Stainless steel AISI 304 (V2A)   |
| <b>Ingress Protection:</b> | IP 56 / Type 12, 3, 3R, 4, 4X    |
| <b>Approvals:</b>          | CE, cURus, cULus                 |
| <b>UL File Number:</b>     | cURus (SA32278), cULus (E498756) |

## Technical Data

|                                              |                                                                          |
|----------------------------------------------|--------------------------------------------------------------------------|
| <b>Cooling capacity L35L35:</b>              | 300 W                                                                    |
| <b>Cooling capacity L35L50:</b>              | 250 W                                                                    |
| <b>Enclosure heater:</b>                     | 150 W                                                                    |
| <b>Compressor type:</b>                      | Rotary piston compressor                                                 |
| <b>Refrigerant / GWP:</b>                    | R 134a / 1430                                                            |
| <b>Refrigerant charge:</b>                   | 96 g / 3.4 oz                                                            |
| <b>High / low Pressure:</b>                  | 29.3 / 6.1 bar<br>425 / 88 psig                                          |
| <b>Operating Temperature Range:</b>          | -40°C - 55°C                                                             |
| <b>Air flow volume (system / unimpeded):</b> | Ambient air circuit: 85 / 300 m³/h<br>Cabinet air circuit: 85 / 136 m³/h |
| <b>Mounting:</b>                             | Wall mounted                                                             |
| <b>Dimensions A x B x C (D+E):</b>           | 480 x 250 x 190 mm                                                       |
| <b>Weight:</b>                               | 15.4 kg                                                                  |
| <b>Cut out dimensions:</b>                   | 204 x 250 mm                                                             |
| <b>Voltage / Frequency:</b>                  | 120 V ~ 60 Hz                                                            |
| <b>UL Voltage / Frequency:</b>               | 115 V ~ 60 Hz                                                            |
| <b>Current L35L35:</b>                       | 2.3 A                                                                    |
| <b>Starting current:</b>                     | 8 A                                                                      |
| <b>Max. current:</b>                         | 2.8 A                                                                    |
| <b>Nominal power L35L35:</b>                 | 260 W                                                                    |
| <b>Max. power:</b>                           | 310 W                                                                    |
| <b>Fuse:</b>                                 | 5 A (T)                                                                  |
| <b>Short-circuit current rating:</b>         | 5 kA                                                                     |
| <b>Connection:</b>                           | Connection terminal block                                                |


Please click on the graphics to download.  
 More CAD drawings can be found under [Product Download](#).  
 > [Overview Product Group COMPACT OUTDOOR - OLD](#)

**Performance graph:**



[click image to enlarge](#)

**Cut Out Dimension:**



[click image to enlarge](#)

## Order Information

|                                                                          |                    |
|--------------------------------------------------------------------------|--------------------|
| <b>In stainless steel 304 (V2A) part no.</b>                             | 57041062           |
| <b>In stainless steel AISI 316 (V4A)</b>                                 | 57041064           |
| <b>In stainless steel 304 (V2A) with 150 W enclosure heater part no.</b> | 57041162           |
| <b>In stainless steel 316 (V4A) with 150 W enclosure heater part no.</b> | 57041164           |
| <b>Box dimensions</b>                                                    | 530 x 298 x 230 mm |
| <b>Gross weight</b>                                                      | 17.5 kg            |
| <b>Taric code</b>                                                        | 84158200           |