



Cabinet cooling unit



Description

Order Number:	850300001
Brand Name:	SLIMLINE PRO
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 55 / Type 12
Approvals:	CE, cURus, cULus
Accessories:	 Gasket Kit Type 4  Cold Air Outlet Duct 8503/06  Washable Aluminium Filter 8503/06  External Transformer 400/460 V 2~

Technical Data

Cooling capacity L35L35:	350 W @ 50 Hz 350 W @ 60 Hz
Cooling capacity L35L50:	200 W @ 50 Hz 215 W @ 60 Hz
EER L35L35:	1.16
Compressor type:	Rotary Piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	100 g / 3.53 oz.
High / low Pressure:	28 / 6 bar 406 / 88 psi
Operating Temperature Range:	10°C - 60°C
UL temperature range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 200 / 408 m³/h Cabinet air circuit: 122 / 180 m³/h
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	600 x 250 x 135 (45+90) mm
Weight:	13.7 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	1.5 A @ 50 Hz 1.3 A @ 60 Hz
Starting current:	4 A
Max. current:	1.6 A
Nominal power L35L35:	300 W @ 50 Hz 300 W @ 60 Hz
Max. power:	355 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	1 A


Full load current fans:	0.2 A
Connection:	4 pole terminal block for power 5 pole terminal block for signals 3 pole terminal block for RS 485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Box dimensions	692 x 350 x 164 mm
Gross weight	14.5 kg
Taric Code	84158200