


Control Cabinet Air Conditioner



Description

Order Number:	43041001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus
Accessories:	Stainless Steel Filter Holder 4304 Fibre Filter Media 4304 Washable Aluminium Filter 4304

Technical Data


Cooling capacity L35L35:	360 W
Cooling capacity L35L50:	220 W
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	79 g / 2.78 oz
High / low Pressure:	25 / 6 bar 365 / 88 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 90 / 250 m³/h Cabinet air circuit: 115 / 136 m³/h
Mounting:	External
Dimensions A x B x C (D+E):	501.6 x 280 x 200 mm
Weight:	26 kg
Cut out dimensions:	480 x 240 mm
Voltage / Frequency:	120 V ~ 60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current L35L35:	4.4 A
Starting current:	12.5 A
Max. current:	5.4 A
Nominal power L35L35:	440 W
Max. power:	550 W
Fuse:	10 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT INDOOR - reliable and economical](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



CUTOUT FOR EXTERNAL

[click image to enlarge](#)

Order Information

Stainless steel housing part no.	4304102
Box dimensions	535 x 323 x 225 mm
Gross weight	27 kg
Taric code	84158200