

Enclosure air conditioner




Description

Order Number:	43151081
Brand Name:	COMPACT INDOOR
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	5,560 BTU
Cooling capacity 95F/122F:	4,500 BTU
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	420 g / 14.8 oz
High / low pressure:	25.5 / 6 bar 370 / 88 psig
Air volume flow (system / unimpeded):	Ambient air circuit: 280 / 500 cfm Cabinet air circuit: 225 / 324 cfm
Operating temperature range:	50°F - 131°F
Mounting:	Recessed
Dimension H x W x D:	41 x 17.8 x 10.6 inch
Weight:	105 lbs.
Cut out dimensions:	15.5 x 36.8 inch
Voltage / Frequency:	120 V ~ 60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current 95F95F:	9.6 A
Starting current:	39.4 A
Max. current:	11.8 A
Nominal power 95F95F:	880 W
Max. power:	1.29 kW
Fuse:	16 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out dimensions:



Order Information

Stainless steel housing part no.	43151026
---	----------

Taric code	84158200
-------------------	----------