

Filter fan SF 4725 - 230V




Description

Order Number:	4725082201
Brand Name:	SOLIVENT PRO
Color:	RAL 7035
Housing Material:	PC plastic / RAL 7035
Ingress protection to EN 60 529:	IP 54
UL Typ (UL 50E):	12
Note:	IP 55 with filter O3 (see manual)
Approvals:	CE, cURus, cULus
UL File Number:	E498756


Technical data

Air flow unimpeded IP 54:	139 / 156 CFM
Air flow with exhaust filter IP 54:	98 / 118 CFM
Air flow unimpeded Type 12:	139 / 156 CFM
Operating temperature range:	14°F - 131°F
Storage temperature range:	-40°F - 158°F
Mounting:	Wall mounted
Dimension H x W x D:	10.06 x 10.06 x 4.43 inches
Cut out dimensions:	8.82 x 8.82 inch
Voltage / Frequency:	230 V ~ 50/60 Hz
Rated current:	0.31 / 0.25 A
Power consumption:	45 / 39 W
Degree of separation IP 54:	67 % - DIN 24185
Degree of separation IP 55:	85 % - DIN 24185
Wall thickness:	0.039 - 0.118 inch
Noise level:	53 dB (A)
Fuse:	1 A (T)
Connection:	Spring terminal


Air flow:



Cooling capacity:



Dimensions:



Order Information

Order number	IP rating	UL Type	RAL colour	Flow type ¹⁾	Air flow (m³/h) ²⁾	Air flow with exhaust filter (m³/h)
4725082203	54	12 / 3R	RAL 9005	B	235 / 264 m³/hr	167 / 200 m³/hr
4725083201	55	12 / 3R	RAL 7035	B	222 / 249 m³/hr	138 / 170 m³/hr
4725083203	55	12 / 3R	RAL 9005	B	222 / 249 m³/hr	138 / 170 m³/hr
472508R2201	54	12 / 3R	RAL 7035	S	238 / 269 m³/hr	
472508R2203	54	12 / 3R	RAL 9005	S	238 / 269 m³/hr	
472508R3201	55	12 / 3R	RAL 7035	S	220 / 252 m³/hr	
472508R3203	55	12 / 3R	RAL 9005	S	220 / 252 m³/hr	

¹⁾ B = Blowing - from ambient into the enclosure (standard version)
S = Suction - from enclosure to ambient (on request)

²⁾ unimpeded 50/60 Hz

Zolltarifnummer

84145915