

Enclosure air conditioner



Description

Order Number:	85259576
Brand Name:	SLIMLINE PRO
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection to EN 60 529:	Type 3, 3R, 12, 4
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/95F:	8530 BTU @ 50 Hz 8530 BTU @ 60 Hz
Cooling capacity 95F/122F:	7165 BTU @ 50 Hz 7165 BTU @ 60 Hz
EER 95F95F:	2.06
Compressor type:	Rotary piston
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	420 g / 14.8 oz
High / low pressure:	30 / 6 bar 435 / 88 psig
Air volume flow (system / unimpeded):	Ambient air circuit: 400 / 706 cfm Cabinet air circuit: 295 / 500 cfm
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 140°F
Mounting:	Wall mounted / recessed
Dimension H x W x D:	1550 x 455 x 292 mm
Weight:	65 kg
Voltage / Frequency:	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
UL Voltage / Frequency:	460 V / 60Hz 3~
Current 95F95F:	2.9 A @ 50 Hz 2.8 A @ 60 Hz
Starting current:	20 A
Max. current:	3.3 A
Nominal power 95F95F:	1270 W @ 50 Hz 1580 W @ 60 Hz
Max. power:	2020 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	2.2 A

Full load current fans:

1.3 A


Connection:

4 pole terminal block for power


5 pole terminal block for signals

3 pole terminal block for RS 485

Performance graph:



Dimensions:



Order Information

Verpackungsmaße	1442 x 495 x 242 mm
Bruttogewicht	50.5 Kg
Zolltarifnummer	84158200