

Enclosure air conditioner



Description

Order Number:	841200S62
Brand Name:	SLIMLINE PRO
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection to EN 60 529:	IP 56 / Type 12, 3, 3R, 4, 4X
Note:	Has the same cutout like KG 8508 and KG 8512
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/95F:	5120 BTU @ 50 Hz 5290 BTU @ 60 Hz
Cooling capacity 95F/122F:	4330 BTU @ 50 Hz 4540 BTU @ 60 Hz
EER 95F95F:	2.1 / 1.8
Compressor type:	Rotary piston
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	267 g / 9.4 oz
High / low pressure:	30 / 6 bar 435 / 88 psi
Air volume flow (system / unimpeded):	Ambient: 323 / 500 m³/h Enclosure: 206 / 500 m³/h
Operating temperature range:	50°F - 140°F
UL temperature range:	50°F - 140°F
Mounting:	Wall mounted / recessed
Dimension H x W x D:	37.5 x 15.6 x 9.9 inch
Weight:	38.5 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	3.3 A @ 50 Hz 3.9 A @ 60 Hz
Starting current:	16 A
Max. current:	5.2 A
Nominal power 95F95F:	700 W @ 50 Hz 860 W @ 60 Hz
Max. power:	960 W @ 50 Hz 1140 W @ 60 Hz
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	2.5 A

Full load current fans:

0.7 A


Connection:

4 - poliger Stecker für Versorgungsspannung

5 - poliger Stecker für Signale

3 - poliger Stecker für RS 485

Dimensions:



Order Information

Box dimensions	1042 x 495 x 283 mm
-----------------------	---------------------

Gross weight	46 Kg
---------------------	-------

Taric code	84158200
-------------------	----------