

SOLITHERM PROTEC



Description

Order Number:	87060584
Brand Name:	SOLITHERM PROTEC
Housing Material:	Stainless steel AISI 316 (V4A)
Ingress protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, UL(ACVS), cULus


Technical data

Cooling capacity 95F/95F:	600 W @ 50 Hz 630 W @ 60 Hz
Cooling capacity 95F/122F:	430 W @ 50 Hz 450 W @ 60 Hz
Enclosure heater:	150 W
Compressor type:	rotary piston compressor
Refrigerant / GWP:	R 134a / 1430
Refrigerant charge:	80 g / 2.8 oz
High / low pressure:	28 / 6 bar 406 / 88 psi
Operating temperature range:	-40°C - 60°C
UL temperature range:	-40°C - 55°C
Air volume flow (system / unimpeded):	Ambient: 235 / 408 m³/h Cabinet: 115 / 180 m³/h
Mounting:	Wall mounted
Dimension H x W x D:	15 x 9.85 x 9.85 inch
Weight:	15.7 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	2.0 A @ 50 Hz 1.9 A @ 60 Hz
Starting current:	6 A
Max. current:	2.3 A
Nominal power 95F95F:	411 W @ 50 Hz 415 W @ 60 Hz
Max. power:	540 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	1.6 A


Full load current fans:	0.2 A
--------------------------------	-------

Connection:	3 core cable for power 5 core cable for signals 3 pole terminal block for RS 485 MODBUS
--------------------	---

Performance graph:



Cut out dimensions:



Order Information

Zolltarifnummer

84158200