

Air to Water Heat Exchanger



Description

Order Number:	751220B001
Brand Name:	SLIMLINE HEX
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 55 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/W50F (53 GPH): 1300 W

Coolant: Water, light oils or similar

Operating temperature range: 1°C - 60°C

Air volume flow (system / unimpeded): 330 / 500 m³/h

Mounting: Wandanbau / Halbeinbau

Dimension H x W x D: 950 x 305 x 192 (37+155) mm

Weight: 16 kg

Voltage / Frequency: 380-415 V 50 Hz 3~
400-460 V 60 Hz 3~

Starting current: 0.4 / 0.4 A

Max. current: 0.2 / 0.2 A

Max. power: 60 / 80 W


Pressure water circuit: 10 bar

Water connection: Rp 3/8" - Innengewinde (mit optionalen Anschlüssen für Rohrrinnendurchmesser von 10 mm)

Fuse: 1 A (T)

Connection: 5-polige Anschlussklemme für Signale
4-polige Anschlussklemme für Spannung

Cut out dimensions:



Order Information

Stainless steel housing part no.	751220B62
Verpackungsmaße	1042 x 405 x 242 mm
Bruttogewicht	21 kg
Taric code	84158300