# Filter Fan



## Description


| | |
|---|---|
| **Order Number:** | 4620A4100 |
| **Brand Name:** | SOLIFLEX |
| **Color:** | RAL 7035 |
| **Housing Material:** | ABS Plastic |
| **Ingress protection:** | IP 54, Type 12, 3R |
| **Note:** | Umgekehrter Luftstrom |
| **Optional:** | Different housing colours available on request<br>With NEMA 3R protection part no. 4620A4130 |
| **Approvals:** | CE, cURus, cULus, CSA |

## Technical data


| | |
|---|---|
| **Operating temperature range:** | 14°F - +131°F |
| **Air volume flow unimpeded:** | 144 cfm / 171 cfm |
| **Static pressure:** | 0.66 inH2O @ 50Hz<br>0.84 inH2O @ 60Hz |
| **Dimension H x W x D:** | 9.8 x 9.8 x 4.9 inch |
| **Weight:** | 3.3 lbs |
| **Cut out dimensions:** | 8.8 x 8.8 (+0.06) inch |
| **Voltage / Frequency:** | 230 V ~ 50/60 Hz |
| **Rated current:** | 0.135 A / 0.16 A |
| **Power consumption:** | 32 W / 36 W |
| **Wall thickness:** | 0.06 - 0.10 in. |
| **Filter class:** | G3 according to EN 779 |
| **Installation:** | Elastic clips or by 4 self-threading screws |
| **Noise level:** | 50 dB(A) @ 50 Hz<br>55 dB(A) @ 60 Hz |


**Air flow:**

Q = Air flow [m3/h]
P = Static pressure [Pa]




**Cut out dimensions**:



## Order Information

| | |
|---|---|
| **In RAL 9005** | 4620A4103 |
| **Taric code** | 84145915 |
| **GTIN (EAN)** | 5350604100541 |