Outdoor air conditioner




Description

Order Number:	4050870
Brand Name:	Compact Outdoor
Color:	RAL 7037
Housing Material:	Mild steel, powder coated
Ingress protection:	NEMA 3R
Note:	Explosion proof according to ATEX / Zone 22 / Category 3D dust
Approvals:	CE

Technical data

Cooling capacity 95F/95F:	15360 BTU
Enclosure heater:	2,000 W
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	3625 g / 127.9 oz
High / low pressure:	40 / 10 bar 580 / 150 psig
Operating temperature range:	-20°C - +40°C
Air volume flow (system / unimpeded):	Ambient air circuit: 1042 / 2615 cfm Cabinet air circuit: 1006 / 1177 cfm
Mounting:	External
Dimension H x W x D:	74.80 x 35.43 x 24.40 inch
Weight:	407.85 lbs
Voltage / Frequency:	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
Current 95F95F:	5.1 A
Starting current:	31 A
Max. current:	31 A
Nominal power 95F95F:	2,500 W
Max. power:	3,500 W
Fuse:	3 x 10 A (T)
Short-circuit current rating:	5 kA
Connection:	WAGO 9-pole connector, male

Performance graph:



Cut out dimensions:

