

Outdoor air conditioner



Description

Order Number:	570910001
Brand Name:	Compact Outdoor
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 56 / Type 12, 3, 3R, 4
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical data

Cooling capacity 95F/95F:	2900 BTU @ 50 Hz 3000 BTU @ 60 Hz
Cooling capacity 95F/122F:	2080 BTU @ 50 Hz 2250 BTU @ 60 Hz
Enclosure heater:	400 W (optional)
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	195 g / 6.9 oz
High / low pressure:	30 / 6.1 bar 435 / 88 psig
Operating temperature range:	-40°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 241 / 500 cfm Cabinet air circuit: 118 / 147 cfm
Mounting:	Wall mounted
Dimension H x W x D:	32.7 x 12 x 10.6 inch
Weight:	83 lbs.
Cut out dimensions:	10.43 x 7.09, 10.43 x 6.3 inch
Voltage / Frequency:	120 V ~ 50/60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current 95F95F:	8.2 A
Starting current:	33 A
Max. current:	8.6 A
Nominal power 95F95F:	640 W
Max. power:	870 W
Fuse:	16 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Order Information

Ohne 400 W Schaltschrankheizung Bestell Nr.	570910001
With 400 W enclosure heater part no.	570911001
Box dimensions	870 x 348 x 310 mm
Gross weight	39 kg
Taric code	84158200