

Enclosure air conditioner type 4X



Description

Order Number:	57090162
Brand Name:	Compact Outdoor
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical data

Cooling capacity 95F/95F:	2900 BTU @ 50 Hz 3000 BTU @ 60 Hz
Cooling capacity 95F/122F:	2080 BTU @ 50 Hz 2250 BTU @ 60 Hz
Enclosure heater:	400 W
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	195 g / 6.9 oz
High / low pressure:	30 / 6.1 bar 435 / 88 psig
Operating temperature range:	-40°C - +55°C
Air volume flow (system / unimpeded):	Ambient air circuit: 241 / 500 cfm Cabinet air circuit: 118 / 147 cfm
Mounting:	Wall mounted
Dimension H x W x D:	32.7 x 12 x 10.6 inch
Weight:	70.54 lbs.
Cut out dimensions:	10.43 x 7.09, 10.43 x 6.3 inch
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	3.0 A @ 50 Hz 3.2 A @ 60 Hz
Starting current:	15 A
Max. current:	3.8 A
Nominal power 95F95F:	530 W @ 50 Hz 610 W @ 60 Hz
Max. power:	870 W
Fuse:	6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Order Information

In Edelstahl 304 (V2A) Bestell Nr.	57090062
With stainless steel AISI 316 (V4A)	57090064
In Edelstahl 304 (V2A) mit 400 W Schaltschrankheizung Bestell Nr.	57090162
In Edelstahl 316 (V4A) mit 400 W Schaltschrankheizung Bestell Nr.	57090164
Verpackungsmaße	870 x 348 x 310 mm
Bruttogewicht	34 kg
Zolltarifnummer	84158200