


Enclosure air conditioner KG 4330-120V Recessed



Product Features

Brand Name:	SoliTherm ComPact
Order Number:	43301081
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	Type 12
Approvals:	CE, cURus, cULus
UL File Nummer:	cURus (SA32278), cULus (E498756)
Accessories:	<p>Fibre filter media</p> <p>Filter holder</p>
Taric Code:	84158200



Technical data KG 4330-120V Recessed

Cooling capacity 95F/95F:	10,240 BTU
Cooling capacity 95F/122F:	8,260 BTU
Compressor:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	900 g / 31.7 oz
High / low pressure:	29.5 / 6 bar 425 / 88 psig
Temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 441 / 706 cfm Cabinet air circuit: 506 / 706 cfm
Mounting:	Recessed
Dimension H x W x D:	51 x 21.9 x 13.4 inch
Weight:	165 lbs.
Cut out dimensions:	19.4 x 48.6 inch
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	15.3 A
Starting current:	49 A
Max. current:	18.4 A
Nominal power 95F95F:	1.37 kW
Max. power:	1.65 kW
Fuse:	20 A (T)
Connection:	Connection terminal block

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview product group Enclosure air conditioners - ComPact Line](#)

