

Outdoor air conditioner




Description

Order Number:	573121201
Brand Name:	Compact Outdoor
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	TYPE 12, 3, 3R, 4
Included:	Mit Schaltschrankheizung und Aluminium Filter
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)


Technical data

Cooling capacity 95F/95F:	10235 BTU
Cooling capacity 95F/122F:	8565 BTU
Enclosure heater:	1500 W
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	820 g / 28.9 oz
High / low pressure:	29 / 6 bar 425 / 88 psig
Operating temperature range:	-40°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 450 / 706 cfm Cabinet air circuit: 560 / 706 cfm
Mounting:	Wall mounted
Dimension H x W x D:	61 x 18 x 14 inch
Weight:	170 lbs.
Voltage / Frequency:	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
UL Voltage / Frequency:	400/460 V ~ 60 Hz 3~
Current 95F95F:	2.1 A @ 50 Hz 2.3 A @ 60 Hz
Starting current:	7.6 A / 8.1 A
Max. current:	3.3 A / 3.5 A
Nominal power 95F95F:	1.34 kW @ 50 Hz 1.70 kW @ 60 Hz
Max. power:	1.66 kW @ 50 Hz 2.10 kW @ 60 Hz
Fuse:	3 x 6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Performance graph:



Cut out dimensions:



Order Information

Box dimensions	1,590 x 503 x 395 mm
Gross weight	82 kg
Taric code	84158200