

Thermoelectric cooler




Description

Order Number:	6805303
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	2730 BTU
Operating temperature range:	-4°F - 149°F
UL temperature range:	-20°C - 65°C
Air volume flow (system / unimpeded):	Ambient air circuit: 280 / 383 cfm Cabinet air circuit: 280 / 383 cfm
Mounting:	recessed
Dimension H x W x D:	972 x 514 x 211 (136,5+74,5) mm
Weight:	146 lbs.
Cut out dimensions:	18.3 x 36.3 inch
Voltage / Frequency:	120 V, 230 V
Current 95F95F:	8.2 A @ 120 V 4.3 A @ 230 V
Starting current:	14 A @ 120 V 8 A @ 230 V
Max. current:	9 A @ 120 V 4.7 A @ 230 V
Nominal power 95F95F:	979 W
Max. power:	1078 W
Fuse:	13 A (T) @ 120 V 7 A (T) @ 230 V
Connection:	4 pole power connector 5 pole connector for signals

Performance graph:



**Cut out
dimensions:**



Order Information

Stainless steel AISI 316 (V4A) housing part no.	68053034
Verpackungsmaße	1060 x 612 x 260 mm
Bruttogewicht	75.5 kg
Taric code	84158300